



(19)

Generated Document.

(11) Publication number:

62278770 A

PATENT ABSTRACTS OF JAPAN

(21) Application number: **61120218**

(51) Intl. Cl.: **H01M 8/06 C21C 5/38**

(22) Application date: **27.05.86**

(30) Priority:

(43) Date of application
publication: **03.12.87**

(84) Designated contracting
states:

(71) Applicant: **NIPPON KOKAN KK <NKK>**

(72) Inventor: **FUJII SHIRO**

(74) Representative:

(54) RECOVERING METHOD OF CO2 AND H2 FROM CONVERTER GAS

(57) Abstract:

PURPOSE: To increase utilization by treating converter gas with a pressure swing adsorber (PSA), treating again with a PSA installed in series, and supplying the obtained H2 to a fuel cell to generate electric power and recovering exhaust heat as steam.

CONSTITUTION: LD converter gas is modified to H2, and treated with a pressure swing adsorber (PSA) 3 through a absorbin tower 1, and offgas RH2 which contains other

gasses in addition to H_2 is stored in a holder 4. The offgas RH_2 is treated with a PSA 6 installed in series to obtain H_2 . The H_2 obtained is supplied to a negative electrode 13 of a fuel cell 15 and reacted with oxygen in a positive electrode 14 to generate electric power. Exhaust gasses from the negative electrode 13 and the positive electrode 14 are supplied to a combustor 18 to completely burn and exhaust heat is recovered in a boiler 19. Therefore, electric power, steam, and fuel gas can be obtained from offgas from purification equipment of converter gas, and utilization is increased.

COPYRIGHT: (C)1987, JPO&Japio

